

SECTION 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name: LOCTITE 577 THREAD SEALANT

Proper Shipping Name: None allocated.

Other Names: LOCTITE 577 FLANGE SEALANT, LOCTITE HIGH PRESSURE 577.

LOCTITE 577 PIPE SEALANT.

Product Code(s): 229930, 281823

Part Number(s): 19259(50 ml), 34112 (250 ml)

Use: Anaerobic sealant for pipe fittings.

Supplier: HENKEL AUSTRALIA PTY. LIMITED ABN 82 001 302 996

ADHESIVE TECHNOLOGIES

135-141 Canterbury Road, Kilsyth, Victoria, 3137. Tel: (03) 9724 6444 24 HOUR EMERGENCY CONTACT NUMBER: Tel: 1800 032 379

SECTION 2. HAZARDS IDENTIFICATION

STATEMENT OF HAZARDOUS NATURE:

Hazardous according to the criteria of Safe Work Australia. This material has been classified as Irritant (Xi).

Risk phrase(s):

R36/37/38 - Irritating to eyes, respiratory system and skin.

R43 - May cause sensitisation by skin contact.

Safety phrase(s):

S24/25 - Avoid contact with skin and eyes.

S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S28 - After contact with skin, wash immediately with plenty of soap suds.

S37/39 - Wear suitable gloves and eye/face protection.

S46 - If swallowed, seek medical advice immediately and show this container or label.

DANGEROUS GOODS INFORMATION:

Not classified as Dangerous Goods according to the criteria of the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG Code).

SUSDP POISON SCHEDULE: None allocated.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENTS:

CHEMICAL ENTITY	CAS NO.	PROPORTION	
Polyglycol dimethacrylate Polyglycol dioctanoate Vinyl resin Alkyl C12 methacrylate Tetradecyl methacrylate 1-Acetyl-2-phenylhydrazine	[25852-47-5] [18268-70-7] [63148-65-2] [142-90-5] [2549-53-3] [114-83-0]	30-60% w/w 10-30% w/w 5-10% w/w 5-10% w/w 1-5% w/w < 1% w/w	

DATE OF ISSUE: 17.08.10 **REVISION OF:** 12.08.05 **IDH NO:** - Page 1 of 4 PRODUCT NAME: LOCTITE 577 THREAD SEALANT



SECTION 4. FIRST AID MEASURES

Ingestion: If swallowed, **do not induce** vomiting. For advice, contact a Poisons Information

Centre (Phone 13 11 26) or a doctor.

Skin: Remove contaminated clothing and wash affected areas with plenty of water. If

irritation, redness or blistering occurs, seek medical attention.

Eyes: Hold eyes open and flush with water for at least 15 minutes. If irritation develops,

seek medical attention.

Inhalation: If inhaled, remove from contaminated area. For all but the most minor

symptoms, arrange for patient to be seen by a doctor.

Advice to doctor: Treat symptomatically.

First Aid facilities: Eye wash and normal washroom facilities. A safety shower is recommended.

SECTION 5. FIRE FIGHTING MEASURES

Suitable extinguishing media: Use foam, dry chemical or carbon dioxide.

Hazards from combustion products: In a fire, it will burn. Under fire conditions, it may release carbon monoxide and noxious fumes.

Precautions for fire fighters and special protective equipment: If there is a risk of exposure to products of combustion, fire-fighters should wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Wear protective gloves, chemical goggles and safety boots. Contain and collect spillage with inert absorbent materials (e.g. sand, earth, vermiculite). Transfer to sealable containers suitable for storing spilled material. Flush areas in contact with spilled material with adequate warm soapy water to render the area safe for human contact. Note: Residues are slightly water soluble. Do not allow to drain or watercourse. Dispose of solid residues in chemical waste disposal area in accordance with relevant State and Federal requirements.

SECTION 7. HANDLING AND STORAGE

Safe Handling: Observe recommendations made under SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION. Use in a well ventilated area. Avoid breathing vapour.

Storage: Store indoors in a cool, dry and well ventilated area. Keep containers sealed when not in use. Store in original containers away from heat, sparks and open flames. Store at or below 38°C.

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

National exposure standards: None established.

Engineering controls: None required under normal conditions of use, but if vapour or mist

is being generated, use a local mechanical exhaust

Personal protective equipment: Use good industrial hygiene. Avoid contact with skin and eyes. Wear overalls, neoprene or butyl rubber gloves and safety glasses with side shields. Use with adequate ventilation. If inhalation risk exists, wear a respirator complying with the requirements of AS 1715 and AS 1716.

DATE OF ISSUE:17.08.10REVISION OF:12.08.05IDH NO:-Page 2 of 4PRODUCT NAME:LOCTITE 577 THREAD SEALANT



SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical data:

Appearance: Dark yellow paste.

Specific gravity: 1.15-1.20

Solubility: Slightly soluble in water

Flash point (PMCC): > 90°C

SECTION 10. STABILITY AND REACTIVITY

Chemical stability: Stable under normal conditions of temperature and pressure.

Conditions to avoid: Open flames, sparks, heat.

Incompatible materials: Keep away from strong oxidising agents, acids and alkalies.

Hazardous decomposition products: Combustible liquid. In a fire, it can release carbon monoxide

and noxious fumes.

Hazardous reactions: None if used for intended purpose.

SECTION 11. TOXICOLOGICAL INFORMATION

HEALTH EFFECTS:

Acute:

Ingestion: If swallowed, may cause gastrointestinal irritation.

Skin: Irritating to skin. May cause sensitisation by skin contact.

Eyes: Contact with the eyes can cause irritation.

Inhalation: Inhalation of vapours may cause respiratory irritation.

Chronic: Repeated or prolonged skin contact may cause chronic dermatitis.

Toxicity information: None available for this product.

SECTION 12. ECOLOGICAL INFORMATION

Do not allow product to contaminate waterways or soil. This product may be harmful to aquatic organisms.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal of this material should be undertaken by a registered chemical disposal company. Empty containers should be disposed of at approved landfill site.

SECTION 14. TRANSPORT INFORMATION

Not classified as Dangerous Goods according to the criteria of the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG Code).

DATE OF ISSUE: 17.08.10 **REVISION OF:** 12.08.05 **IDH NO:** - Page 3 of 4 PRODUCT NAME: LOCTITE 577 THREAD SEALANT



SECTION 15. REGULATORY INFORMATION

SUSDP POISON SCHEDULE: None allocated

SECTION 16. OTHER INFORMATION

Abbreviations/acronyms:

SUSDP - Standard for the Uniform Scheduling of Drugs and Poisons

DISCLAIMER:

The percentage weight (% w/w) of ingredients is not to be taken as a specification guaranteed by Henkel Australia Pty. Limited, but only as an approximate guide to the content of hazardous ingredients in the material. The information contained herein does not constitute a guarantee by Henkel Australia Pty. Limited concerning the properties of the material.

The information contained in this Material Safety Data Sheet is offered in good faith and has been developed from what is believed to be accurate and reliable sources. The information is offered without warranty, representation, inducement or licence and Henkel Australia Pty. Limited assumes no legal responsibility for reliance upon same. Henkel Australia Pty. Limited disclaims any liability for loss, injury or damage incurred in connection with the use of the material or its associated Material Safety Data Sheet.

This information is not to be construed as a representation that the material is suitable for any particular purpose or use except those conditions and warranties implied by either Commonwealth or State statutes. Customers are encouraged to make their own enquiries as to the material's characteristics and, where appropriate, to conduct their own tests in the specific context of the material's intended use.

DATE OF ISSUE: Page 4 of 4 17.08.10 R

REVISION OF: 12.08.05 PRODUCT NAME:

IDH NO: -

LOCTITE 577 THREAD SEALANT